



NOTES

1. STORM SEWERS AND SANITARY SEWERS TO BE LOCATED BETWEEN CURBS.
2. CURB STOPS TO BE LOCATED ON THE PROPERTY LINE.
- A. TELEPHONE, HYDRO AND LIGHTING TO BE LOCATED ON COMMON UTILITY POLE ON EITHER OR BOTH SIDES OF ROAD.
- B. SIDEWALKS MAY BE LOCATED ON EITHER, BOTH OR NEITHER SIDE OF THE ROADWAY.
- C. SIDEWALKS TO BE 1.5m WIDE AND OFFSET 0.6m FROM PROPERTY LINE.
- D. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE SHOWN.

NEW SUBDIVISIONS:

CENTRE LINE LOCATIONS OF UTILITY TRENCHES ON A 20m ROAD ALLOWANCE

DESCRIPTIONS	CURB STOPS	GAS	HYDRO OR JOINT HYDRO TELEPHONE	HYDRANTS	POLES	GLB	WATER MAIN
DISTANCE TO CENTRE LINE OF UTILITY FROM PROPERTY LINE	0.0	0.5	3.0	3.0	3.7	3.7	7.3
MINIMUM DEPTH OF COVER	1.8	1.0	0.9	N/A	N/A	N/A	1.8

REV.6	VARIOUS REVISIONS	08/16
REV.5	REVISED FOR 2016 SPEC.	01/16
REV.4	REVISED FOR 2014 SPEC.	01/14
REV.#	DESCRIPTION	DATE
CITY OF SARNIA		
UTILITY LOCATION LOCAL ROAD 20m ROAD ALLOWANCE		
APPROVED BY:		BK.
DRAWN BY: J.Roberts	SCALE: N.T.S.	DWG.No.
CHK' BY:	DATE: 12/97	114A-F