



NOTES

1. DROPPED CURBS ARE TO BE PROVIDED FOR WIDTH OF ALL PEDESTRIAN CROSSING MARKINGS 1.5m MIN.
2. TACTILE WALKING SURFACE INDICATORS ARE TO BE INSTALLED AT ALL PEDESTRIAN CROSSINGS IN CONJUNCTION WITH ALL ROAD AND SIDEWALK CONSTRUCTION RECONSTRUCTION PROJECTS.
3. EACH LOCATION IS SITE SPECIFIC AND CONSULTATION WITH THE CITY OF SARNIA MAY BE REQUIRED FOR NON TYPICAL INTERSECTIONS AND PEDESTRIAN CROSSINGS.
4. REFER TO 154-F FOR DETAILS ABOUT LOCATION OF TACTILE WALKING SURFACE INDICATORS, CURB CUTS AND SIDEWALK RAMPS.

| | | | |
|-------------------------------------------------------------------------------|----------------|--------------|-------|
| REV.1 | | | |
| REV.# | DESCRIPTION | DATE | AP.BY |
| CITY OF SARNIA | | | |
| SIGNALIZED INTERSECTION CONFIGURATIONS OF PEDESTRIAN CROSSINGS | | | |
| APPROVED BY: | | BK. | |
| DRAWN BY: OD | SCALE: N.T.S. | DWG.No. | |
| CHK' BY: | DATE: FEB 2014 | 153-F | |